



VERODEEP 8 RS

is the strongest non rotation resistant rope in the portfolio with tremendous performance on drum winders.

nominal rope diameter	metallic cross section	rope weight	calculated breaking force		minimum breaking force	
			rope grade		rope grade	
			1770 N/mm ²	1960 N/mm ²	1770 N/mm ²	1960 N/mm ²
mm	mm ²	kg/m	kN	kN	kN	kN
20	215,2	1,851	380,90	421,79	337,10	373,28
21	237,3	2,040	419,94	465,02	371,65	411,55
22	260,4	2,239	460,89	510,37	407,89	451,67
23	284,6	2,448	503,74	557,82	445,81	493,67
24	309,9	2,665	548,50	607,38	485,42	537,53
25	336,2	2,892	595,16	659,05	526,72	583,26
26	363,7	3,128	643,73	712,83	569,70	630,85
27	392,2	3,373	694,19	768,71	614,36	680,31
28	421,8	3,627	746,57	826,71	660,71	731,64
29	452,5	3,891	800,85	886,81	708,75	784,83
30	484,2	4,164	857,03	949,03	758,47	839,89
31	517,0	4,446	915,12	1013,35	809,88	896,82
32	550,9	4,738	975,11	1079,78	862,97	955,61
33	585,9	5,039	1037,01	1148,32	917,75	1016,27
34	621,9	5,349	1100,81	1218,97	974,22	1078,79
35	659,0	5,668	1166,51	1291,73	1032,36	1143,18
36	697,2	5,996	1234,12	1366,60	1092,20	1209,44
37	736,5	6,334	1303,64	1443,58	1153,72	1277,57
38	776,9	6,681	1375,06	1522,66	1216,93	1347,56
39	818,3	7,037	1448,38	1603,86	1281,82	1419,41
40	860,8	7,403	1523,61	1687,16	1348,39	1493,14
41	904,4	7,778	1600,74	1772,57	1416,66	1568,73
42	949,0	8,162	1679,78	1860,09	1486,60	1646,18
43	994,8	8,555	1760,72	1949,73	1558,24	1725,51
44	1041,6	8,957	1843,57	2041,46	1631,56	1806,70
45	1089,4	9,369	1928,32	2135,31	1706,56	1889,75
46	1138,4	9,790	2014,97	2231,27	1783,25	1974,67
47	1188,4	10,221	2103,53	2329,34	1861,63	2061,46
48	1239,5	10,660	2194,00	2429,51	1941,69	2150,12
49	1291,7	11,109	2286,37	2531,80	2023,43	2240,64
50	1345,0	11,567	2380,64	2636,19	2106,87	2333,03
51	1399,3	12,034	2476,82	2742,69	2191,98	2427,28
52	1454,7	12,511	2574,90	2851,30	2278,79	2523,40
53	1511,2	12,997	2674,89	2962,02	2367,28	2621,39
54	1568,8	13,492	2776,78	3074,85	2457,45	2721,24
55	1627,4	13,996	2880,57	3189,79	2549,31	2822,96
56	1687,2	14,510	2986,27	3306,84	2642,85	2926,55